

PATENT**AMENDMENTS TO THE CLAIMS**

Following is a complete set of claims as amended with this Response. This complete set of claims excludes cancelled claims 29 and 34 and includes amended claims 30-33 and 35-42.

1-14. (Cancelled)

15. (Withdrawn) An implantable medical device comprising:

signal processing means for detecting an interatrial conduction disturbance of a heart; and

pulse generator circuit means for delivering atrial arrhythmia prevention pacing pulses to the heart responsive to the detection of the interatrial conduction disturbance.

16. (Withdrawn) The implantable medical device of claim 15, wherein the interatrial conduction disturbance is a P-wave duration in excess of a predetermined criterion and wherein the signal processing means includes P-wave duration timing means for determining durations of detected P-waves.

17. (Withdrawn) The implantable medical device of claim 15, wherein the interatrial conduction disturbance is an average P-wave duration in excess of a predetermined criterion and wherein the signal processing means includes P-wave duration timing means for determining durations of detected P-waves and duration averaging means for averaging determined P-wave durations.

18. (Withdrawn) The implantable medical device of claim 15, wherein the interatrial conduction disturbance is an interatrial delay time in excess of a predetermined criterion, wherein the implantable medical device includes first detecting means for detecting right atrial activations and second detecting means for detecting left atrial activation, and wherein the signal processing means includes interatrial delay timing

PATENT

means for timing interatrial delay times between activations detected by the first detecting means and the second detecting means.

19. (Withdrawn) The implantable medical device of claim 15, wherein the atrial arrhythmia prevention pacing pulses are atrial overdrive pacing pulses and wherein the pulse generator circuit means includes an atrial overdrive pulse generator means for providing atrial overdrive pacing pulses to the heart responsive to the detection of the interatrial conduction disturbance.

20. (Withdrawn) The implantable medical device of claim 15, wherein the pulse generator means includes atrial pacing means for delivering an atrial pacing pulse a delay time after a detected P-wave.

21. (Withdrawn) The implantable medical device of claim 20, further including P-wave duration timing means for determining durations of detected P-waves and control means for varying the delay time responsive to determined P-wave durations.

22. (Withdrawn) The implantable medical device of claim 20, further including P-wave duration timing means for determining durations of detected P-waves and pacing control means for varying the delay time in an inverse relation to determined P-wave durations.

23. (Withdrawn) The implantable medical device of claim 15, wherein the interatrial conduction disturbance is a selected difference between detected odd and even P-waves exceeding a predetermined criterion and wherein the signal processing means includes means for determining if the selected difference between the odd and even P-waves exceeds the predetermined criterion.

24. (Withdrawn) The implantable medical device of claim 15, wherein the interatrial conduction disturbance is a predetermined spectral energy distribution of

PATENT

detected P-waves, and wherein the signal processing means includes spectral analyzing means for performing spectral energy distribution analysis of the detected P-waves.

25. (Withdrawn) The implantable medical device of claim 15, wherein the signal processing means includes a broad field atrial activity detector.

26. (Withdrawn) The implantable medical device of claim 15, wherein the signal processing means includes a near-field atrial activity detector and broad field atrial activity detector.

27. (Withdrawn) The implantable medical device of claim 15, wherein the pulse generator circuit means includes a right atrial pulse generator and left atrial pulse generator.

28. (Withdrawn) The implantable medical device of claim 15, further including pacing control means for causing the pulse generator circuit means to terminate the delivery of atrial arrhythmia prevention pacing pulses to the heart when the interatrial conduction disturbance has subsided.

29. (Currently Cancelled)

30. (Currently Amended) ~~The method of claim 29,~~ A method of pacing a heart to prevent an atrial arrhythmia, the method comprising the steps of:

detecting an interatrial conduction disturbance of the heart; and

delivering atrial arrhythmia prevention pacing pulses to the heart responsive to detecting the interatrial conduction disturbance;

wherein the interatrial conduction disturbance is a P-wave duration in excess of a predetermined criterion and wherein the method further includes comprises the step of determining durations of detected P-waves.

PATENT

31. (Currently Amended) The method of claim 29 30, wherein the interatrial conduction disturbance is an average P-wave duration in excess of a predetermined criterion and wherein the method further ~~includes~~ comprises the steps step of ~~determining durations of detected P-waves and averaging the determined P-wave durations.~~

32. (Currently Amended) The method of claim 29 30, wherein the interatrial conduction disturbance is an interatrial delay time in excess of a predetermined criterion and wherein the method further ~~includes~~ comprises the steps of detecting right atrial activations, detecting left atrial activations, and timing interatrial delay times between right atrial activation detection and left atrial activation detection.

33. (Currently Amended) The method of claim 29 30, wherein the atrial arrhythmia prevention pacing pulses are atrial overdrive pacing pulses and wherein the delivering step ~~includes~~ comprises providing atrial overdrive pacing pulses to the heart.

34. (Currently Cancelled)

35. (Currently Amended) ~~The method of claim 34, A method of pacing a heart to prevent an atrial arrhythmia, the method comprising the steps of:~~

detecting an interatrial conduction disturbance of the heart;

delivering atrial arrhythmia prevention pacing pulses to the heart responsive to detecting the interatrial conduction disturbance;

detecting P-waves of the heart and wherein the delivering step comprises delivering an atrial pacing pulse a delay time after each detected P-wave; and

further including the step of determining durations of detected P-waves and wherein the delivering step further includes comprises varying the delay time responsive to determined P-wave durations.

36. (Currently Amended) The method of claim ~~34~~ 35, ~~further including the step of determining durations of detected P-waves and~~ wherein the delivering step further

PATENT

~~includes~~ comprises varying the delay time in an inverse relation to determined P-wave durations.

37. (Currently Amended) ~~The method of claim 29,~~ A method of pacing a heart to prevent an atrial arrhythmia, the method comprising the steps of:

detecting an interatrial conduction disturbance of the heart;

delivering atrial arrhythmia prevention pacing pulses to the heart responsive to detecting the interatrial conduction disturbance; and

~~further includes the step of~~ detecting P-waves of the heart, wherein the interatrial conduction disturbance is a selected difference between detected odd and even P-waves exceeding a predetermined criterion, and wherein the detecting step ~~includes~~ comprises determining if the selected difference between the odd and even P-waves exceeds a predetermined criterion.

38. (Currently Amended) ~~The method of claim 29,~~ A method of pacing a heart to prevent an atrial arrhythmia, the method comprising the steps of:

detecting an interatrial conduction disturbance of the heart;

delivering atrial arrhythmia prevention pacing pulses to the heart responsive to detecting the interatrial conduction disturbance; and

~~further including the step of~~ detecting P-waves of the heart, wherein the interatrial conduction disturbance is a predetermined spectral energy distribution of detected P-waves, and wherein the method further ~~includes~~ comprises the step of performing spectral energy distribution analysis of the detected P-waves.

39. (Currently Amended) ~~The method of claim 29,~~ A method of pacing a heart to prevent an atrial arrhythmia, the method comprising the steps of:

detecting an interatrial conduction disturbance of the heart; and

delivering atrial arrhythmia prevention pacing pulses to the heart responsive to detecting the interatrial conduction disturbance;

~~including the further step of wherein~~ detecting the interatrial conduction disturbance of the heart comprises sensing broad near-field atrial activity.

PATENT

40. (Currently Amended) ~~The method of claim 29,~~ A method of pacing a heart to prevent an atrial arrhythmia, the method comprising the steps of:
detecting an interatrial conduction disturbance of the heart; and
delivering atrial arrhythmia prevention pacing pulses to the heart responsive to detecting the interatrial conduction disturbance;
~~including the further step of~~ wherein detecting the interatrial conduction disturbance of the heart comprises sensing near-field atrial activity and far-field atrial activity.
41. (Currently Amended) The method of claim 29 30, wherein the delivery step includes delivering right atrial pacing pulses and left atrial pacing pulses.
42. (Currently Amended) The method of claim 29 30, further including the step of terminating the delivery of the atrial fibrillation prevention pacing pulses to the heart when the interatrial conduction disturbance ceases.